



AMBER

AMBER PREPRINT

•

Amber Preprint is a high white, technically advanced, uncoated paper, developed for direct mail, invoices, letterheads and advertising material. The paper complies with the requirements of DIN 6723 and 6724-1 standards which mean that the paper is guaranteed to work on equipment with optical character recognition (OCR). Amber Preprint works perfectly in digital presses and is also guaranteed to work in laser printers, even after offset litho printing. Thanks to its properties it can be used in high speed photocopiers and printers. Amber Preprint is available in both sheets and reels. Amber Preprint standard products are available as FSC™ – The mark of responsible forestry. www.fsc.org. FSC-C022692 and PEFC certified.

AMBER

AMBER PREPRINT

•

Grammage (g/m ²)	Opacity (%)	Thickness (µm)	Whiteness (CIE)	Roughness (Bendtsen, ml/min)
70^E	≥92	91	167	160
80	≥93	104	167	160
90	≥95	117	167	200
100	≥96	130	167	200
120	≥98	156	167	200
160	≥99	208	167	230

Screen recommended 133-150 lpi

^E Not standard production. Min. 30 tonnes and paper machine trim needed.

Values are targets only and can be subject to changes over time without prior notice.

AMBER PREPRINT
SPECIFICATIONS

•
BASIC INFORMATION



Optimized for
colour printing



Available in
sheets



Available in
reels



Uncoated



Coated



Smooth



Rough

Surface



Highwhite White Cream

Shade

•
ENVIRONMENT / SAFETY



FSC
www.fsc.org
FSC® C022692

FSC



PEFC
PEFC/05-37-113
Promoting sustainable forest
management
www.pefc.org

PEFC



ECF



ISO 14001



EMAS



Paper Profile



Safety of Toys



Food contact



Age resistant
(ISO 9706)



Woodfree

•
PRINTING TECHNIQUES



Offset



Flexo



Laser



Preprint



Inkjet
(black/white)

×