## **G-PRINT**

G-Print is a woodfree coated paper. High bulk, generous paper feel and excellent runability, making G-Print a great paper choice. Smooth yet bulky it is noted for its consistent technical quality. The smooth, low-reflecting surface provides both perfect readability and quality image reproduction, with high gloss contrast. G-Print offers sharp, even print and low mottling tendencies. Finishing performance provides unique folding and binding properties. G-Print is ideal for books, magazines, brochures, catalogues, covers, direct mail, folders, posters, inserts and maps. G-Print is available both as sheets and reels in various sizes in grammages from 70 to 300 g/m<sup>2</sup>. G-Print standard products are available as FSC<sup>™</sup> and PEFC certified.



# GPRINT

#### BASIC INFORMATION

Optimized for colour printing. Available in sheets. Available in reels

#### ENVIRONMENT / SAFETY

The paper is inspected for Nordic Ecolabelled printing , ECF, ISO 14001, EMAS, Paper Profile, Safety of Toys , Age resistant (ISO 9706), Woodfree, FSC\_C007342, PEFC\_053398

#### PRINTING TECHNIQUES

Offset (heatset), Offset (sheet-fed), Flexo, Laser, HP Indigo

#### SHADE

White

### SURFACE

Coated, Matt

#### **G-PRINT**

Grammage (g/m²)	70	80	90	100	115	130	150	170	200	250	300
Opacity (%)	87.5	90.5	92	93.5	96	97	98	98.5	99	99.5	99.5
Thickness (µm)	68	77	87	98	113	129	150	172	203	255	318
Bulk (thickness/grammage)	0.96	0.96	0.97	0.98	0.98	0.99	1.0	1.01	1.02	1.02	1.06
Whiteness (CIE)	117	117	117	117	117	117	117	117	119	119	119
Brightness (ISO 2470/D65 %)	95	95	95	95	95	95	95	95	97	97	97
Smoothness (PPS, µm)	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.2	2.2	2.8
Surface Gloss (TAPPI T 480: 75°, g.u.)	<25	<25	<25	<25	<25	<25	<25	<25	<30	<30	<30

Screen recommended, max 175 lpi

Values are targets only and can be subject to changes over time without prior notice.